

FL 637 - Dados técnicos



Description

FL 637 é um pneu radial Flotation apropriado para espalhadores, reboques e cisternas móveis. A estrutura com cintos em aço garante durabilidade superior e maior capacidade de carga. Além das excelentes propriedades de flutuação que se traduzem numa compactação reduzida, este pneu apresenta extraordinárias propriedades de autolimpagem. O desenho direcional do piso do pneu assegura uma tração excepcional alcançando velocidades até 70 km/h.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Espalhador • Cisterna móvel • Reboque

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
520/50 R 17	STANDARD	94054909	151D/148E	16.00		20.3	37.5	16.3	115.4	TL	E11-106R-004070
560/45 R 22.5	STANDARD	94074174	160D	AG 16.00		21.4	42.4	19.7	130.9	TL	E11-106R-008660

Printed on 19/04/2024 03:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..