

FLOTATION 351 - Especificações técnicas



Description

FLOTATION 351 é um pneu diagonal Flotation ideal para aplicações no transporte com reboques. Os ganchos extra profundos fornecem uma tração extraordinária e prolongam a vida do pneu. FLOTATION 351 é o pneu ideal para superfícies molhadas e húmidas que assegura uma capacidade de carga elevada.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Reboque

Version	STANDARD
Type	TL
Tyre Size	48 X 25.00 - 20
LI/SS	144 B

Dimensions International Standard

Ply Rating	10
Section Width (mm)	630
Overall Diameter (mm)	1270
Static Loaded Radius (mm)	559
Rolling Circumference (mm)	3785
Rim Rec	20.50 HF
Rim Alt	20.50 VF
TRA Code	HF3

Load capacity (Kg)

km/h / bar	2.40
50	2800

Printed on 27/04/2024 04:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..