

FLOTATION 647 - Especificações técnicas



Description

FLOTATION 647 é um pneu para implementos agrícolas que fornece uma tração excelente em terrenos brandos e em prados. Além de propriedades de auto limpeza avançadas, o desenho especial do piso mostra uma ampla área de contacto que assegura uma distribuição otimizada do peso e prestações excelentes em terreno brando.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricultura: Implementos agrícolas

Version	STANDARD
Type	TL
Tyre Size	520/50 - 17
LI/SS DRIVE WHEEL	147 B
LI/SS FREE ROLLING	159 B

Dimensions US Standard

Usa code	94063314
Section Width (inch)	20.3
Overall Diameter (inch)	38
Static Loaded Radius (inch)	16.8
Rolling Circumference (inch)	114.4
Rim Rec	AG 16.00
ECE	E11-106R-005770

Load capacity (lbs)

mph / psi	58
30 FR	9650
30 DW	6800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/02/2025 15:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..