

FLOTATION 647 - Dados técnicos



Description

FLOTATION 647 é um pneu para implementos agrícolas que fornece uma tração excelente em terrenos brandos e em prados. Além de propriedades de auto limpeza avançadas, o desenho especial do piso mostra uma ampla área de contacto que assegura uma distribuição otimizada do peso e prestações excelentes em terreno brando.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Implementos agrícolas

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
260/75 - 15.3	STANDARD	119 A8	131 A8	9.00		275	785	363	2380	TL	E11-106R-005838
520/50 - 17	STANDARD	147 B	159 B	AG 16.00		516	965	426	2907	TL	E11-106R-005770
425/70 - 18	STANDARD	143 B	155 B	13.00		435	1065			TL	E11-106R-005851

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/02/2025 14:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..