

## FLOTATION 648 - Especificações técnicas



### Description

FLOTATION 648 é especialmente idóneo para transportes no campo e na estrada e aplicações de espalhadores. Algumas medidas são apropriadas para ceifeiras/prensas para fardos de palha. O desenho especial do piso do pneu permite o transporte de cargas muito pesadas com pressões baixas, garantindo, por conseguinte, uma compactação reduzida do solo, protegendo as culturas de prejuízos.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Enfardadeira de feno • Ceifeira • Espalhador

Version	HD
Type	TL
Tyre Size	650/65 - 30.5
LI/SS DRIVE WHEEL	169 A8/165 B
LI/SS FREE ROLLING	181 A8/178 B

## Dimensions International Standard

<b>Ply Rating</b>	18
<b>Section Width (mm)</b>	670
<b>Overall Diameter (mm)</b>	1660
<b>Static Loaded Radius (mm)</b>	710
<b>Rolling Circumference (mm)</b>	4935
<b>Rim Rec</b>	AG 20.00
<b>ECE</b>	E11-106R-004563

## Load capacity (Kg)

km/h / bar	2.30	2.40	2.50
10 FR	10995	11275	11550
20 FR	9895	10150	10395
30 FR	8800	9020	9240
40 FR	7855	8055	8250
50 FR	7070	7250	7500
10 DW	7735	7930	8120
20 DW	6960	7140	7310
30 DW	6190	6345	6495
40 DW	5525	5665	5800
50 DW	4975	5100	5150

Printed on 17/04/2024 23:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..