

## FLOTATION 648 - Especificações técnicas



### Description

FLOTATION 648 é especialmente idóneo para transportes no campo e na estrada e aplicações de espalhadores. Algumas medidas são apropriadas para ceifeiras/prensas para fardos de palha. O desenho especial do piso do pneu permite o transporte de cargas muito pesadas com pressões baixas, garantindo, por conseguinte, uma compactação reduzida do solo, protegendo as culturas de prejuízos.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Enfardadeira de feno • Ceifeira • Espalhador

Version	HD
Type	TL
Tyre Size	700/40 - 22.5
LI/SS DRIVE WHEEL	160 A8/156 B
LI/SS FREE ROLLING	173 A8/169 B

## Dimensions US Standard

Usa code	94027903
Ply Rating	18
Section Width (inch)	27.6
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	20.1
Rolling Circumference (inch)	139.3
Rim Rec	AG 24.00
ECE	E4-106R-002281

## Load capacity (lbs)

mph / psi	41	44	46
5 FR	18550	19230	20060
10 FR	16700	17390	18050
20 FR	14840	15450	16050
25 FR	13250	13800	14330
30 FR	11930	12420	12790
5 DW	12840	13380	13890
10 DW	11550	12040	12500
20 DW	10270	10700	11110
25 DW	9170	9560	9920
30 DW	8260	8600	8820

Printed on 17/04/2024 22:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..