

FLOTATION 648 - Especificações técnicas



Description

FLOTATION 648 é especialmente idóneo para transportes no campo e na estrada e aplicações de espalhadores. Algumas medidas são apropriadas para ceifeiras/prensas para fardos de palha. O desenho especial do piso do pneu permite o transporte de cargas muito pesadas com pressões baixas, garantindo, por conseguinte, uma compactação reduzida do solo, protegendo as culturas de prejuízos.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Ceifeira • Espalhador

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 700/50 - 22.5 |
| LI/SS DRIVE WHEEL | 162 A8/158 B |
| LI/SS FREE ROLLING | 174 A8/170 B |

Dimensions International Standard

| | |
|-----------------------------------|----------------|
| Ply Rating | 16 |
| Section Width (mm) | 700 |
| Overall Diameter (mm) | 1270 |
| Static Loaded Radius (mm) | 550 |
| Rolling Circumference (mm) | 3775 |
| Rim Rec | 24.00 |
| ECE | E4-106R-001566 |

Load capacity (Kg)

| km/h / bar | 2.00 | 2.20 | 2.40 |
|------------|------|------|------|
| 10 FR | 8430 | 8910 | 9380 |
| 20 FR | 7585 | 8020 | 8440 |
| 30 FR | 6740 | 7130 | 7505 |
| 40 FR | 6020 | 6365 | 6700 |
| 50 FR | 5420 | 5730 | 6000 |
| 10 DW | 5980 | 6320 | 6650 |
| 20 DW | 5380 | 5690 | 5985 |
| 30 DW | 4780 | 5055 | 5320 |
| 40 DW | 4270 | 4515 | 4750 |
| 50 DW | 3845 | 4065 | 4250 |

Printed on 17/04/2024 18:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..