

FLOTATION 648 - Especificações técnicas



Description

FLOTATION 648 é especialmente idóneo para transportes no campo e na estrada e aplicações de espalhadores. Algumas medidas são apropriadas para ceifeiras/prensas para fardos de palha. O desenho especial do piso do pneu permite o transporte de cargas muito pesadas com pressões baixas, garantindo, por conseguinte, uma compactação reduzida do solo, protegendo as culturas de prejuízos.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Ceifeira • Espalhador

Version	STANDARD
Type	TL
Tyre Size	700/50 - 26.5
LI/SS DRIVE WHEEL	157 A8/154 B
LI/SS FREE ROLLING	169 A8/165 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	700
Overall Diameter (mm)	1373
Static Loaded Radius (mm)	621
Rolling Circumference (mm)	4099
Rim Rec	24.00
ECE	E4-106R-002278

Load capacity (Kg)

km/h / bar	1.50	1.60	1.80
10 FR	7300	7580	8120
20 FR	6570	6825	7310
30 FR	5840	6065	6495
40 FR	5215	5415	5800
50 FR	4695	4875	5150
10 DW	5195	5390	5775
20 DW	4675	4850	5200
30 DW	4155	4310	4620
40 DW	3710	3850	4125
50 DW	3340	3465	3750

Printed on 17/04/2024 23:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..