

FLOTATION 648 - Especificações técnicas



Description

FLOTATION 648 é especialmente idóneo para transportes no campo e na estrada e aplicações de espalhadores. Algumas medidas são apropriadas para ceifeiras/prensas para fardos de palha. O desenho especial do piso do pneu permite o transporte de cargas muito pesadas com pressões baixas, garantindo, por conseguinte, uma compactação reduzida do solo, protegendo as culturas de prejuízos.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Ceifeira • Espalhador

Version	STANDARD
Type	TL
Tyre Size	800/45 - 26.5
LI/SS DRIVE WHEEL	164 A8/160 B
LI/SS FREE ROLLING	177 A8/173 B

Dimensions US Standard

Usa code	94006564
Ply Rating	16
Section Width (inch)	31.5
Overall Diameter (inch)	54.8
Static Loaded Radius (inch)	24.8
Rolling Circumference (inch)	164.8
Rim Rec	AG 28.00
ECE	E4-106R-002280

Load capacity (lbs)

mph / psi	26	29	32
5 FR	20030	21310	22530
10 FR	18020	19180	20280
20 FR	16030	17050	18020
25 FR	14310	15220	16090
30 FR	12870	13700	14330
5 DW	13720	14590	15430
10 DW	12350	13140	13890
20 DW	10980	11680	12350
25 DW	9800	10430	11020
30 DW	8820	9380	9920

Printed on 17/04/2024 23:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..