

FLOTATION RIB IMPLEMENT - Especificações técnicas

Description

FLOTATION RIB IMPLEMENT é um pneu com nervuras específicas para reboques, implementos agrícolas e compressores de palha nas aplicações de transporte e de recolha da palha. O pneu destaca-se pela capacidade elevada de carga e um ciclo de vida prolongado.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas
• Reboque



Version	STANDARD
Type	TL
Tyre Size	31 X 13.50 - 15
LI/SS	124 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	360
Overall Diameter (mm)	780
Static Loaded Radius (mm)	374
Rolling Circumference (mm)	2398
Rim Rec	10 LB
ECE	E11-106R-003389

Load capacity (Kg)

km/h / bar	5.20
50	1600

Printed on 26/04/2024 06:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..