

FLOTATION TR 675 - Especificações técnicas



Description

FLOTATION TR 675 é ideal tanto para no transporte no campo como o na estrada. Pode ser utilizado em reboques e implementos agrícolas. FLOTATION 675 foi projetado para fornecer uma tração sensacional, uma capacidade de carga elevada e um ciclo de vida prolongado do produto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Implementos agrícolas • Reboque

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 550/60 - 22.5 |
| LI/SS DRIVE WHEEL | 148 A8/144 B |
| LI/SS FREE ROLLING | 160 A8/156 B |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94019809 |
| Ply Rating | 12 |
| Section Width (inch) | 21.7 |
| Overall Diameter (inch) | 49.6 |
| Static Loaded Radius (inch) | 21.5 |
| Rolling Circumference (inch) | 143.3 |
| Rim Rec | AG 16.00 |
| ECE | E11-106R-004396 |

Load capacity (lbs)

| mph / psi | 22 | 26 | 30 |
|-----------|-------|-------|-------|
| 5 FR | 11410 | 12690 | 13890 |
| 10 FR | 10260 | 11420 | 12500 |
| 20 FR | 9130 | 10150 | 11110 |
| 25 FR | 8150 | 9060 | 9920 |
| 30 FR | 7330 | 8160 | 8820 |
| 5 DW | 7980 | 8880 | 9720 |
| 10 DW | 7180 | 8000 | 8750 |
| 20 DW | 6380 | 7110 | 7780 |
| 25 DW | 5700 | 6350 | 6940 |
| 30 DW | 5130 | 5710 | 6170 |

Printed on 23/04/2024 17:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..