

FLOTATION TR 678 - Especificações técnicas



Description

FLOTATION TR 678 foi especialmente desenvolvido para implementos agrícolas e reboque, tanto na estrada como fora da estrada. Permite transportar cargas pesadas de baixas pressões, assegurando ao mesmo tempo uma compactação reduzida no solo. Este pneu garante uma excelente tração e ótimas propriedades de autolimpagem.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Implementos agrícolas • Reboque

Version	INDUSTRIAL
Type	TL
Tyre Size	600/40 - 22.5
LI/SS DRIVE WHEEL	157 A8
LI/SS FREE ROLLING	169 A8

Dimensions International Standard

Ply Rating	20
Section Width (mm)	615
Overall Diameter (mm)	1085
Static Loaded Radius (mm)	483
Rolling Circumference (mm)	3264
Rim Rec	AG 20.00

Load capacity (Kg)

	km/h / bar	4.10
	40 FR	5800
	40 DW	4125

Printed on 23/02/2024 13:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..