

FLOTATION TR 678 - Especificações técnicas



Description

FLOTATION TR 678 foi especialmente desenvolvido para implementos agrícolas e reboque, tanto na estrada como fora da estrada. Permite transportar cargas pesadas de baixas pressões, assegurando ao mesmo tempo uma compactação reduzida no solo. Este pneu garante uma excelente tração e ótimas propriedades de autolimpagem.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Implementos agrícolas • Reboque

Version	STEEL BELTED
Type	TL
Tyre Size	710/40 - 22.5
LI/SS	173 A8

Dimensions International Standard

Section Width (mm)	707
Overall Diameter (mm)	1165
Static Loaded Radius (mm)	545
Rolling Circumference (mm)	3624
Rim Rec	AG 24.00
ECE	E11-106R-006011

Load capacity (Kg)

km/h / bar	6.0
40	6500

Printed on 26/02/2024 21:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..