

## FLOTATION V LINE - Especificações técnicas



### Description

FLOTATION V LINE foi especificadamente concebido para reboques nas aplicações de transporte. O pneu revela capacidades elevadas de flutuação, assegurando uma compactação reduzida do solo para proteger o seu campo. FLOTATION V LINE permite-lhe transportar cargas pesadas com baixas pressões, otimizando a produtividade da sua empresa.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Reboque

Version	STANDARD
Type	TL
Tyre Size	500/60 - 22.5
LI/SS DRIVE WHEEL	145 A8/142 B
LI/SS FREE ROLLING	157 A8/154 B

## Dimensions International Standard

<b>Ply Rating</b>	12
<b>Section Width (mm)</b>	500
<b>Overall Diameter (mm)</b>	1170
<b>Static Loaded Radius (mm)</b>	510
<b>Rolling Circumference (mm)</b>	3489
<b>Rim Rec</b>	AG 16.00
<b>Rim Alt</b>	15.00 ; 17.00
<b>ECE</b>	E4-106R-001561

## Load capacity (Kg)

km/h / bar	1.50	2.00	2.40
10 FR	4390	5195	5775
20 FR	3950	4675	5200
30 FR	3510	4155	4620
40 FR	3135	3710	4125
50 FR	2820	3340	3750
10 DW	3085	3645	4060
20 DW	2780	3280	3655
30 DW	2470	2920	3250
40 DW	2205	2605	2900
50 DW	1985	2345	2650

Printed on 20/04/2024 11:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..