

## FLOTATION V LINE - Especificações técnicas



### Description

FLOTATION V LINE foi especificadamente concebido para reboques nas aplicações de transporte. O pneu revela capacidades elevadas de flutuação, assegurando uma compactação reduzida do solo para proteger o seu campo. FLOTATION V LINE permite-lhe transportar cargas pesadas com baixas pressões, otimizando a produtividade da sua empresa.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Reboque

Version	STANDARD
Type	TL
Tyre Size	500/60 - 22.5
LI/SS DRIVE WHEEL	151 A8/ 148 B
LI/SS FREE ROLLING	163 A8/159 B

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	500
<b>Overall Diameter (mm)</b>	1170
<b>Static Loaded Radius (mm)</b>	510
<b>Rolling Circumference (mm)</b>	3489
<b>Rim Rec</b>	AG 16.00
<b>Rim Alt</b>	15.00 ; 17.00
<b>ECE</b>	E4-106R-001562

## Load capacity (Kg)

km/h / bar	2.80	3.00	3.20
10 FR	6315	6575	6825
20 FR	5685	5915	6145
30 FR	5050	5260	5460
40 FR	4510	4695	4875
50 FR	4060	4225	4375
10 DW	4465	4650	4830
20 DW	4020	4185	4345
30 DW	3575	3720	3865
40 DW	3190	3320	3450
50 DW	2870	2990	3150

Printed on 20/04/2024 12:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..