

FLOTATION V LINE - Dados técnicos



Description

FLOTATION V LINE foi especificadamente concebido para reboques nas aplicações de transporte. O pneu revela capacidades elevadas de flutuação, assegurando uma compactação reduzida do solo para proteger o seu campo. FLOTATION V LINE permite-lhe transportar cargas pesadas com baixas pressões, otimizando a produtividade da sua empresa.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Reboque

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
500/60 - 22.5	STANDARD	145 A8/142 B	157 A8/154 B	12	AG 16.00	15.00 ; 17.00	500	1170	510	3489	TL	E4-106R-001561
500/60 - 22.5	STANDARD	151 A8/ 148 B	163 A8/159 B	16	AG 16.00	15.00 ; 17.00	500	1170	510	3489	TL	E4-106R-001562
550/60 - 22.5	STANDARD	148 A8/144 B	160 A8/ 156 B	12	AG 16.00		550	1240	540	3725	TL	
550/60 - 22.5	STANDARD	154 A8/150 B	167 A8/163 B	16	AG 16.00		550	1240	540	3725	TL	E4-106R-001563

Printed on 20/04/2024 05:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..