FORESTECH - Especificações técnicas

Description

FORESTECH é um pneu BKT com cintos em aço, apropriado para aplicações florestais com máquinas forwarder (autocarregadoras). O pneu proporciona uma tração excelente, mesmo em condições de serviço pesado. O calcanhar robusto e a área da pá fortificada, asseguram uma resistência elevada às perfurações e uma vida mais longa do pneu. Portanto, poderá realizar, sem preocupações, as operações mais exigentes e difíceis na floresta.

UM

US Standard

Construction

BIAS

Machinery

Agricultura: Autocarregadora

Version	STEEL BELTED
Type	TL
Tyre Size	750/55 - 26.5
LI/SS	177 A8/184 A2

Dimensions US Standard

Usa code	94031719
Ply Rating	20
Section Width (inch)	29.7
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	175.9
Rim Rec	AG 24.00
ECE	E11-106R-003347
TRA Code	LS2

Load capacity (lbs)

mph / psi	73
25	16090
20	17220
5	19840

Printed on 23/04/2024 10:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..