

FORESTECH - Dados técnicos



Description

FORESTECH é um pneu BKT com cintos em aço, apropriado para aplicações florestais com máquinas forwarder (autocarregadoras). O pneu proporciona uma tração excelente, mesmo em condições de serviço pesado. O calcanhar robusto e a área da pá fortificada, asseguram uma resistência elevada às perfurações e uma vida mais longa do pneu. Portanto, poderá realizar, sem preocupações, as operações mais exigentes e difíceis na floresta.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Autocarregadora

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
710/40 - 22.5	STEEL BELTED	LS2	161 A8/ 165 A2	20	AG 24.00		710	1165	550	3612	TL	E11-106R-005273
600/55 - 26.5	STEEL BELTED	LS2	165 A8/172 A2	20	AG 20.00		610	1335	618	4032	TL	E11-106R-003419
710/45 - 26.5	STEEL BELTED	LS2	168 A8/175 A2	20	AG 24.00		710	1340	620	4047	TL	E11-106R-003420
750/55 - 26.5	STEEL BELTED	LS2	177 A8/184 A2	20	AG 24.00		755	1485	680	4467	TL	E11-106R-003347

Printed on 19/04/2024 20:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..