

FORESTLAND - Especificações técnicas



Description

O FORESTLAND é o mais recente e inovador padrão agroflorestal da BKT. Este pneu diagonal foi especialmente concebido para condições de utilização intensiva na exploração florestal, mas também pode ser utilizado em algumas operações agrícolas como paisagismo e palhagem. O FORESTLAND é um pneu particularmente robusto graças à sua forte lona de carcaça em poliéster. Adicionalmente, o composto especial para o piso com resistência a cortes e "chips", juntamente com uma parede lateral forte, asseguram uma longa vida útil do pneu mesmo nas condições de trabalho mais difíceis.

Enquanto o design de ombro aberto proporciona uma excelente tração em solo solto, o padrão do piso especial e os blocos rígidos e reforçados permitem uma boa aderência em qualquer solo além das melhores propriedades de autolimpeza. Além disso, a construção forte do talão garante uma estabilidade de alto nível em operações de uso intensivo.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Trator

Version	STANDARD
Type	TT
Tyre Size	18.4 - 38
LI/SS	155 A8 / 152 B

Dimensions US Standard

Usa code	94074037
Ply Rating	14
Section Width (inch)	18.4
Overall Diameter (inch)	68.9
Static Loaded Radius (inch)	32
Rolling Circumference (inch)	212
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-008167
TRA Code	LS2

Load capacity (lbs)

mph / psi	38
25	8550
30	7850

Printed on 28/04/2024 19:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..