

FS 216 - Especificações técnicas



Description

FS 216 revela um desenho robusto dos ganchos com angulação otimizada e mais larga para potenciar as performances em tema de tração para máquinas forwarder (autocarregadoras) e máquinas de arrasto skidder. O pneu proporciona uma resistência excelente aos cortes e aos rasgões, mesmo em condições operacionais mais críticas, assegurando, em cada momento, a máxima proteção contra possíveis danos.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Trator florestal skidder

Version	STEEL BELTED
Type	TL
Tyre Size	DH 35.5L - 32

Dimensions International Standard

Ply Rating	24
Section Width (mm)	907
Overall Diameter (mm)	2011
Static Loaded Radius (mm)	912
Rolling Circumference (mm)	5992
Rim Rec	DH 31
Rim Alt	DH 31 H
TRA Code	LS2

Load capacity (Kg)

km/h / bar	2.10	2.40
10	-	11200
30	8000	-

Printed on 23/04/2024 22:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..