

## GF 304 - Especificações técnicas



### Description

GF 304 é um pneu apropriado para aplicações de golfe com carrinhos de golfe. GF 304 assegura o máximo conforto e uma ótima proteção do terreno. GF 304 também está disponível em versão "aramid belted", com cintos em aramida, para fornecer uma resistência maior à perfuração.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Carrinho de golf

Version	ARAMID BELTED
Type	TL
Tyre Size	18 X 8.50 - 8

## Dimensions US Standard

Usa code	94008056
Ply Rating	4
Section Width (inch)	8.5
Overall Diameter (inch)	18.1
Static Loaded Radius (inch)	8
Rolling Circumference (inch)	52.5
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005218

## Load capacity (lbs)

mph / psi	22
10	825

Printed on 23/04/2024 04:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..