

## GIANT TRAX - Especificações técnicas



### Description

GIANT TRAX foi desenvolvido para pás skid steer que operam em superfícies ásperas, como as que se podem encontrar nos parques de sucatas e nas aplicações de reciclagem e mineiras. O piso do pneu super profundo, com blocos mais largos e mais robustos, assegura uma ótima tração, estabilidade e resistência à perfuração. O especial composto de borracha do piso traduz-se numa resistência extraordinária aos cortes e lacerações, associada com a resistência excelente contra o desgaste em todos os tipos de terreno.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Minicarregadora

Version	STANDARD
Type	TL
Tyre Size	14 - 17.5

## Dimensions US Standard

Usa code	94064403
Ply Rating	14
Section Width (inch)	13.8
Overall Diameter (inch)	36
Static Loaded Radius (inch)	16.6
Rolling Circumference (inch)	106.9
Rim Rec	10.50
ECE	E11-106R-006019

## Load capacity (lbs)

mph / psi	80
5	8540
10	6750
15	6240

Printed on 22/04/2024 18:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..