

## GR 288 - Especificações técnicas



### Description

GR 288 (G-2/L-2) é um pneu versátil, com carcaça diagonal para niveladoras ou pás carregadoras. O pneu é ideal para ser utilizado no setor das construções, na preparação do local, nas construções de estradas, bem como em outros ambientes macios ou com lama. O desenho do piso tem ótimas propriedades de autolimpagem, que se traduzem numa tração excelente. Graças ao especial composto resistente a cortes e rasgões, o pneu assegura um ciclo de vida longo.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Trator de esteira • Carregadora  
OTR: Motoniveladora

Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

## Dimensions International Standard

Ply Rating	16
Overall Width (mm)	520
Overall Diameter (mm)	1480
Static Loaded Radius (mm)	656
Rolling Circumference (mm)	4396
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
ECE	E11-106R-005405
TRA Code	G2/L2

## Load capacity (Kg)

km/h / bar	2.25	3.50
40	4000	-
10	-	8250

Printed on 23/04/2024 15:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..