

## I - 1 - Especificações técnicas



### Description

I-1 foi projetado para o transporte no campo e na estrada, bem como para as operações para trabalhar o terreno com implementos agrícolas e reboques. I-1 é um pneu de alta velocidade, que otimiza os tempos de deslocamento, de modo que poderá concentrar-se na sua atividade principal. O desenho especial do piso do pneu assegura uma vida operacional longa, mesmo em condições mais críticas e em presença de restolhos insidiosos no campo.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Implementos agrícolas • Reboque

Version	STANDARD
Type	TL
Tyre Size	11L - 15 SL
LI/SS	118 D

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	270
Overall Diameter (mm)	770
Static Loaded Radius (mm)	342
Rolling Circumference (mm)	2256
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-004547
TRA Code	I1

## Load capacity (Kg)

km/h / bar	3.00
65	1320

Printed on 08/12/2023 03:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..