

I - 1 - Especificações técnicas



Description

I-1 foi projetado para o transporte no campo e na estrada, bem como para as operações para trabalhar o terreno com implementos agrícolas e reboques. I-1 é um pneu de alta velocidade, que otimiza os tempos de deslocamento, de modo que poderá concentrar-se na sua atividade principal. O desenho especial do piso do pneu assegura uma vida operacional longa, mesmo em condições mais críticas e em presença de restolhos insidiosos no campo.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Implementos agrícolas • Reboque

Version	STANDARD
Type	TL
Tyre Size	21.5L - 16.1 SL

Dimensions US Standard

Usa code	94052738
Ply Rating	18
Section Width (inch)	22.4
Overall Diameter (inch)	45.3
Static Loaded Radius (inch)	19.5
Rolling Circumference (inch)	138.2
Rim Rec	W 18 CH
Rim Alt	W 16 CH
ECE	E11-106R-004301
TRA Code	I1

Load capacity (lbs)

mph / psi	44
40	8800

Printed on 18/04/2024 03:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..