

INDUSTRIAL RIB F3 - Especificações técnicas



Description

INDUSTRIAL RIB F3 é um pneu agro-industrial com desenho do piso por blocos, projetado para o transporte no campo e na estrada, bem como para as operações de trabalho do terreno com implementos agrícolas e reboques. Este pneu destaca-se pela resistência extraordinária aos restos, que o torna apropriado para as condições operacionais mais críticas, assegurando um ciclo de vida longo do produto.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Implementos agrícolas • Reboque

Version	STANDARD
Type	TL
Tyre Size	11L - 15 SL
LI/SS	114 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	279
Overall Diameter (mm)	813
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-004302
TRA Code	F3

Load capacity (Kg)

km/h / bar	3.60
30	1185
40	1060

Printed on 26/04/2024 22:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..