

## IT 400 - Especificações técnicas



### Description

IT 400 é um pneu com desenho do piso por blocos para ser utilizado na estrada nas aplicações de transporte para reboque baixo. O pneu é apropriado para aplicações de alta velocidade e garante uma poupança significativa de combustível.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Reboque baixo

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 7.50 - 15 |
| LI/SS     | 125/121 J |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94008278        |
| Ply Rating                   | 16              |
| Section Width (inch)         | 8.3             |
| Overall Diameter (inch)      | 31.3            |
| Static Loaded Radius (inch)  | 14              |
| Rolling Circumference (inch) | 93              |
| Rim Rec                      | 6.0             |
| Rim Alt                      | 5.50 F ; 6.50   |
| ECE                          | E11-54R-0019535 |

## Load capacity (lbs)

| mph / psi | 125  | 115  |
|-----------|------|------|
| 62 LS     | 3650 | -    |
| 62 LD     | -    | 3210 |

Printed on 23/04/2024 17:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..