

## IT 400 - Dados técnicos



### Description

IT 400 é um pneu com desenho do piso por blocos para ser utilizado na estrada nas aplicações de transporte para reboque baixo. O pneu é apropriado para aplicações de alta velocidade e garante uma poupança significativa de combustível.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Reboque baixo

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.00 - 15	STANDARD	137/133 J	14	7.5	7.0 ; 8.0	274	925	408	2747	TT	E11-54R-0018587
10.00 - 15	STANDARD	141/136 J	16	7.5	7.0 ; 8.0	274	925	408	2747	TT	E11-54R-0018588
10.00 - 15	STANDARD	143/138 J	18	7.5	7.0 ; 8.0	274	925	408	2747	TT	E11-54R-0019537
7.50 - 15	STANDARD	125/121 J	16	6.0	5.50 F ; 6.50	210	795	356	2361	TT	E11-54R-0019535
8.25 - 15	STANDARD	129/125 J	14	6.50	6.0 ; 7.0	239	846	377	2513	TL	E11-54R-0018586
8.25 - 15	STANDARD	131/126 J	16	6.50	6.0 ; 7.0	239	846	377	2513	TT	E11-54R-0019536
8.25 - 15	STANDARD	129/125 J	14	6.50	6.0 ; 7.0	239	846	377	2513	TT	E11E11-54R-0018586

Printed on 23/04/2024 18:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..