

LG 306 - Especificações técnicas



Description

LG 306 é um pneu para prados e jardinagem, apropriado para máquinas de cortar relva. Em algumas medidas, LG 306 também é apropriado para pequenos tratores. O desenho específico do piso do pneu torna o pneu delicado no terreno, facilitando, ao mesmo tempo, o manuseamento e as manobras. LG 306 está disponível numa versão "aramid-belted", com cintos em aramida, para utilizadores que exigem uma maior resistência à perfuração.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Máquina de cortar relva • Trator pequeno

| | |
|--------------------|----------------------------------|
| Version | IMPLEMENT |
| Type | TL |
| Tyre Size | 260/55 - 12 (23 X 10.50 - 12) |
| LI/SS DRIVE WHEEL | 110 A8 |
| LI/SS FREE ROLLING | 122 A8 |

Dimensions International Standard

| | |
|----------------------------|-------------------------------|
| Ply Rating | 14 |
| Section Width (mm) | 260 |
| Overall Diameter (mm) | 585 |
| Static Loaded Radius (mm) | 262 |
| Rolling Circumference (mm) | 1697 |
| Rim Rec | 8.5 I - 55 |
| Rim Alt | 7.00 I - 55 ; I - 70 ; I - 90 |
| ECE | E11-106R-006955 |

Load capacity (Kg)

| km/h / bar | 6.00 |
|------------|------|
| 40 FR | 1500 |
| 40 DW | 1060 |

Printed on 23/04/2024 08:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..