

LG 408 - Dados técnicos



Description

LG 408 é um pneu para prados e jardinagem, apropriado para máquinas de cortar relva e tratores pequenos. O desenho específico do piso do pneu torna o pneu delicado no terreno, prevenindo danos ao relvado facilitando, ao mesmo tempo, o manuseamento e as manobras. LG 408 está disponível numa versão "aramid belted", com cintos em aramida, para utilizadores que exigem uma maior resistência à perfuração.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Máquina de cortar relva • Trator pequeno

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
24 X 13.00 - 12	ARAMID BELTED	6	10.5 I - 55 ; I - 70 ; I - 90		325	610	269	1755	TL	E11-106R-003364
24 X 13.00 - 12	STANDARD	4	10.5 I - 55 ; I - 70 ; I - 90		325	610	269	1755	TL	E11-106R-005204
24 X 13.00 - 12	STANDARD	6	10.5 I - 55 ; I - 70 ; I - 90		325	610	269	1755	TL	E11-106R-003464
26.5 X 14.00 - 12	ARAMID BELTED	6	12.00 I		380	665	293	1929	TL	E11-106R-005223
26.5 X 14.00 - 12	STANDARD	4	12.00 I		380	665	293	1929	TL	E11-106R-005205
26.5 X 14.00 - 12	STANDARD	6	12.00 I		380	665	293	1929	TL	E11-106R-003353
26.5 X 14.00 - 12	STANDARD	10	12.00 I		380	665	293	1929	TL	E11-106R-004650

Printed on 27/04/2024 11:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..