

LG RIB PLUS - Especificações técnicas



Description

O LG RIB PLUS é um pneu para relvados e jardins adequado para utilização com corta-relvas, tratores pequenos e viradores.

O padrão do piso foi especialmente desenhado para garantir um contacto delicado com o solo e, assim, evitar danos na relva, além de facilitar a manobrabilidade.

O perfil arredondado permite ao LG RIB PLUS deslizar e arrastar facilmente ao virar.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Máquina de cortar relva • Trator pequeno

Version	STANDARD
Type	TL
Tyre Size	16 X 6.50 - 8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	170
Overall Diameter (mm)	408
Rim Rec	5.375 I - 55 ; I - 70 ; I - 90

Load capacity (Kg)

km/h / bar	4.90
15	480

Printed on 08/06/2023 13:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..