

LG SMOOTH - Especificações técnicas



Description

LG SMOOTH é um pneu para prados e jardinagem, apropriado para máquinas de cortar relva. Enquanto o pneu é delicado no terreno, o desenho avançado assegura um aumento da duração e facilita o manuseamento e as manobras. LG SMOOTH está disponível numa versão "aramid belted", com cintos em aramida, para utilizadores que exigem uma maior resistência à perfuração.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Máquina de cortar relva • Trator pequeno

Version	STANDARD
Type	TL
Tyre Size	18 X 10.50 - 10

Dimensions International Standard

Ply Rating	2
Section Width (mm)	254
Overall Diameter (mm)	460
Static Loaded Radius (mm)	207
Rolling Circumference (mm)	1334
Rim Rec	8.5 I - 55 ; I - 70 ; I - 90
Rim Alt	8½ JA
ECE	E11-106R-005203

Load capacity (Kg)

km/h / bar	0.80
15	334

Printed on 25/04/2024 21:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..