

LIFTMAX LM 63 - Especificações técnicas



Description

O LIFTMAX LM 63 foi especificamente concebido para operações industriais e logísticas. O design com piso de 3 nervuras proporciona uma baixa resistência ao rolamento com uma boa aderência em terrenos molhados e um desgaste uniforme do piso, o que garante uma melhor manobrabilidade. É um pneu radial com lona de carcaça em aço integral (All Steel) de várias camadas que proporciona baixas vibrações, bem como uma estabilidade e um conforto melhorados.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira

Industrial: Tow Tractor • Reboque

Version	STANDARD
Type	TL
Tyre Size	180/70 R 8 IMP (18X7 R 8)
LI/SS	120 A8

Dimensions International Standard

Overall Width (mm)	170
Overall Diameter (mm)	460
Rim Rec	4.33R
ECE	E11-106R-006845

Load capacity (Kg)

km/h / bar	10.00
40	1400

Printed on 26/04/2024 00:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..