

LIFTMAX LM 63 - Especificações técnicas



Description

O LIFTMAX LM 63 foi especificamente concebido para operações industriais e logísticas. O design com piso de 3 nervuras proporciona uma baixa resistência ao rolamento com uma boa aderência em terrenos molhados e um desgaste uniforme do piso, o que garante uma melhor manobrabilidade. É um pneu radial com lona de carcaça em aço integral (All Steel) de várias camadas que proporciona baixas vibrações, bem como uma estabilidade e um conforto melhorados.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira

Industrial: Tow Tractor • Reboque

Version	STANDARD
Type	TL
Tyre Size	7.00 R 12
LI/SS	136 A5

Dimensions International Standard

Overall Width (mm)	195
Overall Diameter (mm)	675
Rim Rec	5.00S

Load capacity (Kg)

km/h / bar	10.00
25	2240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 03:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..