

LOADER PLUS - Especificações técnicas



Description

LOADER PLUS (L-3) é um pneu com estrutura diagonal, projetado particularmente para carregadores. O composto de borracha do piso proporciona características de resistência a todo o tipo de corte e é ideal para operações de carregamento e nivelção.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Trator de esteira • Carregadora

OTR: Trator de esteira • Carregadora

Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	540
Overall Diameter (mm)	1490
Static Loaded Radius (mm)	685
Rolling Circumference (mm)	4410
Rim Rec	17.00/2.0
TRA Code	L3

Load capacity (Kg)

km/h / bar	3.50
10	8250

Printed on 25/04/2024 20:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..