

LT TR 182 - Especificações técnicas



Description

LT TR 182 é apropriado para operações de transporte com caminhões ligeiros. Este pneu de alta velocidade, é utilizado principalmente na estrada e reduz claramente o consumo de combustível. O pneu LT TR 182 também é fácil de montar.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Camião ligeiro

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

Dimensions International Standard

Ply Rating	12
Section Width (mm)	207
Overall Diameter (mm)	710
Rim Rec	6.00 MH

Load capacity (Kg)

	km/h / bar	6.90
	100 LS	1285
	100 LD	1130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/10/2024 01:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..