

MAGLIFT ECO RIB - Dados técnicos



Description

MAGLIFT ECO RIB foi concebido particularmente para reboques de equipamentos de apoio no solo. A sua estrutura reforçada elimina o risco de deslize, enquanto o especial bordo de proteção da jante protege o pneu dos danos. MAGLIFT ECO RIB assegura o comando da direção excelente, estabilidade elevada, baixa vibração assim como auto-alinhamento do reboque. Vantagens adicionais são a baixa resistência ao rolamento e a reduzida geração de calor, otimizando la eficiência.

UM

US Standard

Construction

◆ SOLID

Machinery

Industrial: Empilhador

SIZE	Version	USACode	RIM REC	RIM ALT	SW	OD	Type
4.00 - 8	STANDARD	94062157	3.00 D - 8		4.1	16	
4.00 - 8	STANDARD	94062706	3.75 I - 8		4.9	16.1	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 22:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..