MAGLIFT ECO - Especificações técnicas

Description

MAGLIFT ECO foi concebido particularmente para aplicações com empilhadores. O pneu é caracterizado por uma estabilidade elevada e a distribuição otimizada de carga. A sua estrutura reforçada elimina o risco de deslize, enquanto o especial bordo de proteção da jante protege o pneu da danos. MAGLIFT ECO assegura uma excelente tração como uma baixa resistência ao rolamento e ao calor, otimizando la eficiencia.

UM

US Standard

Construction

- SOLID

Machinery

Industrial: Empilhador

Version	STANDARD
Type	
Tyre Size	23 X 9 - 10 (225 / 75 - 10)

Dimensions US Standard

Usa code	94065424
Section Width (inch)	7.2
Overall Diameter (inch)	22.8
Rim Rec	6.50 F - 10

Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	7595
15 STEER WHEEL	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 04:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..