

## MAGLIFT ECO - Especificações técnicas



### Description

MAGLIFT ECO foi concebido particularmente para aplicações com empilhadores. O pneu é caracterizado por uma estabilidade elevada e a distribuição otimizada de carga. A sua estrutura reforçada elimina o risco de deslize, enquanto o especial bordo de proteção da jante protege o pneu de danos. MAGLIFT ECO assegura uma excelente tração como uma baixa resistência ao rolamento e ao calor, otimizando a eficiência.

### UM

International Standard

### Construction

◆ SOLID

### Machinery

Industrial: Empilhador

Version

STANDARD

Type

Tyre Size

8.15-15/28x9-15  
(225/75-15)

## Dimensions International Standard

Section Width (mm)	204
Overall Diameter (mm)	691
Rim Rec	7.0 - 15

## Load capacity (Kg)

km/h / bar	-
25 LOAD WHEEL	3445
25 STEER WHEEL	2650

Printed on 24/04/2024 06:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..