

MAGLIFT - Especificações técnicas



Description

MAGLIFT foi especificadamente projetado para empilhadores nos setores industriais e na logística. Este pneu cheio destaca-se pela sua capacidade elevada de carga e um conforto excepcional. MAGLIFT proporciona uma resistência excelente a todo o tipo de corte, que se traduz num ciclo de vida prolongado do pneu. A estrutura reforçada do pneu reduz o risco de deslize, enquanto a especial forma do talão facilita a montagem na jante.

UM

International Standard

Construction

◆ SOLID

Machinery

Industrial: Empilhador

Version

LIP - NON MARKING

Type

Tyre Size

18 X 7 - 8
(180/70 - 8)

Dimensions International Standard

TKPH	1
Section Width (mm)	153
Overall Diameter (mm)	457
Rim Rec	4.33 R - 8

Load capacity (Kg)

	km/h / bar	
	25 LOAD WHEEL	2145
	25 STEER WHEEL	1650

Printed on 27/04/2024 18:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..