

MAGLIFT - Especificações técnicas



Description

MAGLIFT foi especificadamente projetado para empilhadores nos setores industriais e na logística. Este pneu cheio destaca-se pela sua capacidade elevada de carga e um conforto excepcional. MAGLIFT proporciona uma resistência excelente a todo o tipo de corte, que se traduz num ciclo de vida prolongado do pneu. A estrutura reforçada do pneu reduz o risco de deslizamento, enquanto a especial forma do talão facilita a montagem na jante.

UM

US Standard

Construction

◆ SOLID

Machinery

Industrial: Empilhador

Version

STANDARD - NON MARKING

Type

Tyre Size

7.50 - 15

Dimensions US Standard

| | |
|-------------------------|----------|
| Usa code | 94054527 |
| Section Width (inch) | 7.6 |
| Overall Diameter (inch) | 29.8 |
| Rim Rec | 6.0 - 15 |

Load capacity (lbs)

| mph / psi | - |
|----------------|------|
| 15 LOAD WHEEL | 8600 |
| 15 STEER WHEEL | 6615 |

Printed on 28/04/2024 04:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..