

MH TR 182 - Especificações técnicas



Description

MH TR 182 é apropriado para veículos que transportam casas móveis. O pneu de alta velocidade, para ser utilizado principalmente na estrada, proporciona uma poupança significativa de combustível. MH TR 182 assegura uma longa duração e prestações elevadas durante todo o ciclo de vida do produto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Casa móvel

| | |
|-----------|----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 8 - 14.5 |

Dimensions US Standard

| | |
|-------------------------|----------|
| Usa code | 94008599 |
| Ply Rating | 12 |
| Section Width (inch) | 8.1 |
| Overall Diameter (inch) | 28 |
| Rim Rec | 6.00 MH |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 100 |
| 62 | 2835 |

Printed on 22/02/2024 22:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..