

MINE STAR - Especificações técnicas



Description

MINE STAR é um pneu de lonas cruzadas, que representa uma ótima escolha de serviço pesado nas minas. O pneu destaca-se pela resistência elevada a cortes/rasgões e perfurações, otimizando a eficiência operacional.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Veículo para minas subterrâneas

Version	STANDARD
Type	TT
Tyre Size	35 X 15 - 15

Dimensions International Standard

Ply Rating	20
Section Width (mm)	372
Overall Diameter (mm)	885
Rim Rec	11.0
Rim Alt	11.50 ; 11.00 BD

Load capacity (Kg)

km/h / bar	9.00
10	5130

Printed on 25/04/2024 19:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..