

MINEFORCE - Especificações técnicas



Description

O MINEFORCE é um pneu diagonal especialmente projetado para camiões de transporte em operações de mineração e pedreiras. O pneu MINEFORCE de alto desempenho para camiões de transporte é a resposta inovadora da BKT a ambientes rochosos, abrasivos e duros de mineração. Com compostos especialmente desenvolvidos, o design do piso foi concebido para trabalhos em minas difíceis, rochosos e exigentes. A grande zona de contacto com porcas rígidas proporciona um desgaste uniforme do piso e um ciclo de vida mais longo.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dumper Rígido

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 27.00 - 49 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Ply Rating | 48 |
| TKPH | 475 |
| Overall Width (mm) | 740 |
| Overall Diameter (mm) | 2695 |
| Static Loaded Radius (mm) | 1253 |
| Rolling Circumference (mm) | 7985 |
| Rim Rec | 19.50/4.0 |
| TRA Code | E4 |

Load capacity (Kg)

| km/h / bar | 5.75 | 7.75 |
|------------|-------|-------|
| 50 | 25000 | - |
| 10 | - | 43750 |

Printed on 26/04/2024 15:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..