

## MP 585 - Especificações técnicas



### Description

MP 585 é um pneu agroindustrial apropriado para veículos polivalentes nas obras municipais e na manutenção. O pneu foi especificadamente projetado com um desenho do piso de blocos que proporciona uma máxima estabilidade e uma ótima durabilidade em condições operacionais mais difíceis, mesmo em altas velocidades.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Veiculo universal

Industrial: Veiculo universal

Version	STANDARD
Type	TT
Tyre Size	6.50 - 20
LI/SS	38 A8

## Dimensions US Standard

Usa code	94051243
Ply Rating	10
Section Width (inch)	7.9
Overall Diameter (inch)	34.4
Rim Rec	5.50 F
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-004308

## Load capacity (lbs)

mph / psi	80
25	1650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 22:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..