

MP 590 - Especificações técnicas



Description

MP 590 é um pneu agroindustrial idóneo para operações de carga com levantadores telescópicos e empilhadoras. O pneu proporciona uma ótima tração e uma estabilidade excelente junto com uma maior durabilidade.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Levantador telescópico

Industrial: Empilhador • Levantador telescópico • Veículo universal

Version	STANDARD
Type	TL
Tyre Size	18 - 22.5 (445/65 - 22.5)

Dimensions US Standard

Usa code	94014729
Ply Rating	16
Section Width (inch)	18.9
Overall Diameter (inch)	46.9
Static Loaded Radius (inch)	20.9
Rolling Circumference (inch)	139.1
Rim Rec	14.0
ECE	E11-106R-003019

Load capacity (lbs)

mph / psi	80
25 DW	10750
20 DW	12010

Printed on 23/04/2024 14:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..