

## MP 600 - Especificações técnicas



### Description

MP 600 é um pneu agroindustrial idóneo para aplicações de obras municipais e na manutenção com levantadores telescópicos e implementos agrícolas que fornece uma experiência de condução confortável. O pneu proporciona uma ótima tração e propriedades excelentes de autolimpagem, bem como um ciclo de vida prolongado do produto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Implementos agrícolas • Levantador telescópico

Industrial: Levantador telescópico • Veículo universal

Version	STANDARD
Type	TL
Tyre Size	12.5 - 18

## Dimensions International Standard

<b>Ply Rating</b>	12
<b>Section Width (mm)</b>	308
<b>Overall Diameter (mm)</b>	990
<b>Static Loaded Radius (mm)</b>	450
<b>Rolling Circumference (mm)</b>	2950
<b>Rim Rec</b>	11
<b>Rim Alt</b>	12 SDC

## Load capacity (Kg)

	km/h / bar	3.50
	40 DW	2300
	50 DW	2240

Printed on 09/12/2023 23:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..