

MUD POWER HD - Especificações técnicas



Description

MUD POWER HD foi concebido especificadamente para minicarregadoras. O desenho profundo do piso do pneu, para além da disposição especial das barras do pneu, assegura uma excelente tração em terreno molhado e macio. MUD POWER HD foi realizado com um composto de borracha industrial especial e é caracterizado por uma carcaça robusta em nylon que garantem um ciclo de vida mais prolongado também em condições severas.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Minicarregadora

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions US Standard

Usa code	94057818
Ply Rating	10
Section Width (inch)	12.4
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	15.4
Rolling Circumference (inch)	99
Rim Rec	9.75
ECE	E11-106R-005563
TRA Code	R4

Load capacity (lbs)

mph / psi	65
5	5600
10	4420
15	4090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/01/2025 20:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..