

## MULTIMAX MP 515 - Especificações técnicas



### Description

MULTIMAX MP 515 é um pneu radial agro-industrial projetado para veículos universais e camiões de fertilizantes. É idóneo para aplicações de municipalidade e de transporte. O pneu apresenta um desenho único do piso do pneu, que se traduz num grande conforto na condução na estrada bem como propriedades excelentes de autolimpagem e uma excelente tração. A carcaça robusta em nylon com cintos em aço e o ombro reforçado asseguram uma durabilidade elevada. MULTIMAX MP 515 é o pneu perfeito, mesmo a velocidades elevadas (90km/h).

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Veículo universal • Camião de fertilizantes

Version	STANDARD
Type	TL
Tyre Size	405/70 R 20 MPT
LI/SS	136 G

## Dimensions US Standard

Usa code	94056545
Section Width (inch)	16
Overall Diameter (inch)	42.4
Static Loaded Radius (inch)	19.4
Rolling Circumference (inch)	129.4
Rim Rec	13
Rim Alt	13 SDC ; 12 SDC ; 11 SDC ; 11
ECE	E4-54R-0016565

## Load capacity (lbs)

mph / psi	23	29	36	44	51
55	2950	3480	4010	4500	4940
40	3210	3780	4350	4880	5370
25	3410	4010	4620	5180	5690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/05/2025 14:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..