

MULTIMAX MP 519 - Dados técnicos



Description

MULTIMAX MP 519 é um pneu particularmente adequado para caminhões ligeiros em todas as aplicações de transporte. A carcaça reforçada com cintas de aço garante uma estabilidade excelente a velocidades elevadas (90 km/h). Graças à baixa resistência de rodagem, o pneu assegura consumos reduzidos de combustível.

UM

US Standard

Construction



RADIAL

Machinery

Industrial: Camião ligeiro

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
7.50 R 16 LT	STANDARD	94063437	112/110G	8	6.00	5.50 F ; 6 L ; 7 L	8.7	31.9	14.8	96.4	TL	E11-54R-0019046
7.50 R 16 LT	STANDARD	94053384	109/107 G	6	6.00	5.50 F ; 6 L ; 7 L	8.7	31.9	14.8	96.4	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/05/2025 20:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..